# SAFETY DATA SHEET according to regulation (EC) No.1907/2006

# **SECTION 1: Identification of the substance/mixture and company**

## 1.1. Product Identifier

Product code: A3BS2

Name: Brake Safe Plus

**1.2. Product Uses** Solvent brake and clutch cleaner. Do not use on flexible hydraulic pipes or internal hydraulic parts.

1.3. Supplier Quadralene Ltd

Bateman Street

Derby DE23 8JL

Phone: 01332 292500 Web: www.quadralene.co.uk

Fax: 01332 295941

Email: info@quadralene.co.uk

# 1.4. Emergency telephone number

Emergency telephone number: 01332 292402

# SECTION 2: Hazards identification (Undiluted product)

#### 2.1. Classification of the mixture

**According to 1272/2008** 

Health Hazards: Asp. Tox. 1, Eye Irrit. 2, Skin Irrit. 2, STOT SE 3

Physical Hazards: Flam. Liq. 2 Environmental Hazards: Aquatic Chronic 2

# 2.2. Label elements According to 1272/2008

Danger







H225 Highly flammable liquid and vapour

H304 May be fatal if swallowed and enters airways

H315 Causes skin irritation H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

H411 Toxic to aquatic life with long lasting effects

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P260 Do not breathe mist/vapours/spray.

P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

# 2.3. Other hazards

## **SECTION 3: Composition/information on ingredients**

Material	CAS number	Level	Hazards (see section 16)	
Hydrocarbons C6-& n-alkanes, isoalkanes, cyclics	921-024-6	55-100%	Aquatic Chronic 2, Asp. Tox. 1, Flam. Liq. 2, Skin Irrit. 2, STOT SE 3	H225 H315 H336 H304 H411
Propan-2-ol	67-63-0	10-40%	Eye Irrit. 2, Flam. Liq. 2, STOT SE 3	H225 H319 H336
Acetone	67-64-1	10-40%	Eye Irrit. 2, Flam. Liq. 2, STOT SE 3	H225 H319 H336
n-Hexane	110-54-3	1-6%	Aquatic Chronic 2, Asp. Tox. 1, Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT RE 2, STOT SE 3	H225 H315 H361F H336 H373 H304 H411

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

Eye contact: Immediately flush eyes with water, holding eyelids apart, for at least 10 minutes. Seek medical assistance

immediately.

Skin contact: Remove contaminated clothing, wash skin with soap and water. Seek medical attention if irritation persists.

Inhalation: In case of overexposure, remove to fresh air, keep warm and at rest, seek medical assistance immediately.

Ingestion: Do not induce vomiting. Seek medical assistance immediately.

First aider PPE: As required to prevent contact. See section 8.2.

#### 4.2. Most important symptoms and effects, both acute and delayed

Eye hazard: Will cause irritation.

Skin hazard: Will cause irritation.

Respiratory

Excessive exposure may cause irritation of the respiratory tract, headache, dizziness and nausea.

hazard:

Other hazards: Main danger is lung damage by aspiration.

## 4.3. Indication of any immediate medical attention and special treatment needed

#### **SECTION 5: Fire fighting measures**

Flammability hazard: Highly flammable.

## 5.1. Extinguishing media

Use foam, dry powder or carbon dioxide.

## 5.2. Special hazards arising from the mixture

May produce toxic fumes under extreme heating in fire. Forms explosive mixtures with air. May travel considerable distance to source of ignition

## 5.3. Advice for firefighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Take precautions to avoid contact. Use Personal Protective Equipment as detailed in section 8

Exclude sources of ignition, provide ventilation. Spillage may make floors slippery. Keep the area clear. Observe regulations.

## 6.2. Environmental precautions

Prevent spills from entering water courses.

# 6.3. Methods and material for containment and cleaning up

Exclude sources of ignition, provide ventilation.

Absorb using sand or other inert material and transfer to suitable containers for disposal.

#### 6.4. Reference to other sections

Observe the advice given in sections 8 and 13

#### **SECTION 7: Handling and storage**

Shelf life: 24 months in original sealed containers.

#### 7.1. Precautions for safe handling

Do not mix with other products. Observe good industrial hygiene.

Keep away from sources of ignition. Provide ventilation.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, dry place protected from frost and away from acids, strong oxidising agents and sources of ignition. Store upright in original containers. Recommended storage temperature 5-25°C.

#### 7.3. Product Uses

Apply by brush or low pressure spray. Brush to remove grease and dust. Reapply as necessary. Allow to dry. When cleaning brakes, test operation after use.

Please refer to product safety data sheet before use. Use only as directed.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

Workplace exposure limits

 Acetone
 500ppm
 WEL 8 hour TWA (UK EH40)

 n-Hexane
 72mg/m³
 WEL 8 hour TWA (UK EH40)

 Propan-2-ol
 400ppm
 WEL 8 hour TWA (UK EH40)

## 8.2. Exposure controls

These measures are suggested on the basis of general use methods and may not be appropriate to all potential uses of the product. The user is responsible for carrying out a full risk assessment of their specific processes and systems of work.

Eye protection: Wear eye protection to BS EN 166 1F if splashing is likely.

Hand protection: Wear nitrile or neoprene gloves. Exact choice of glove depends on specific risk assessments.

Body protection: As necessary to prevent contact.

Respiratory Use in a well ventilated area. Avoid breathing vapour or spray. Wear a respirator if necessary.

protection:

Other protection: LEV should be considered for large or frequent use

Personal protective equipment:







Exact PPE requirements should be determined from a specific risk assessment of the processes being carried out.

Environmental protection: Prevent mixture from entering water courses.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Appearance: Colourless liquid
Odour: Characteristic

pH (typical): Not applicable

Initial boiling point: 63-100°C. Flash point: <0°C.

Auto-ignition temp: ~200°C Viscosity: Free flowing.

Explosive properties: No data
Oxidising properties: None.
Vapour pressure: No data

Solubility: Approximately 20% in water

Relative density at 20° C (typical): 0.72

#### 9.2. Other information

# **SECTION 10: Stability and reactivity**

**10.1. Reactivity** Incompatible with strong oxidising agents and acids.

**10.2. Chemical stability** Stable under recommended storage conditions.

**10.3.** Possibilty of hazardous reactions No hazardous reactions are expected to occur.

10.4. Conditions to avoid Extremes of temperature, flames.

**10.5.** Incompatible materials Incompatible with strong oxidising agents and acids.

**10.6.** Hazardous decomposition products May produce toxic fumes in fire.

# **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity: Based on available data, the classification criteria are not met.

Skin corrosion/ irritation: Mixture is classified as Skin Irrit. 2. See section 2.

Serious eye damage/ irritation: Mixture is classified as Eye Dam. 2. See section 2.

Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT single exposure: Mixture is classified as STOT SE 3. See section 2.

STOT repeated exposure: Based on available data, the classification criteria are not met.

Aspiration toxicity: Mixture is classified as Asp Tox. 1. See section 2.

## Routes of exposure/ symptoms

Eye contact: Will cause irritation.

Skin contact: Will cause irritation.

Inhalation: Excessive exposure may cause irritation of the respiratory tract, headache, dizziness and nausea.

Ingestion: Low toxicity. Main danger is of aspiration.

#### **SECTION 12: Ecological information**

12.1. Toxicity May affect aquatic organisms due to hydrocarbon content if released into water courses untreated.

12.2. Persistence and degradability

Toxic to aquatic life with long lasting effects

**12.3. Bioaccumulative potential**Not expected to bioaccumulate

**12.4. Mobility in soil**This product has no water solubility

**12.5. Results of PBT and vPvB assessment**Contains no ingredients classified as PBT or vPvB.

**12.6.** Other adverse effects No other adverse effects are anticipated.

## **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

Dispose of surplus product and packaging via a licenced chemical waste contractor.

Dispose of used cloths carefully - fire hazard.

## **SECTION 14: Transport information**

**14.1. UN number** 1993 **14.2. UN proper shipping name** Flammable Liquid, N.O.S.

14.3. Transport hazard class(es) 3 14.4. Packing group 2

**14.5. Environmental hazards**Toxic to aquatic life with long lasting effects for supply

**14.6. Special precautions for user** No specific precautions.

14.7. Transport in bulk according to Annex II of MARPOL 7 3/78 and the IBC Code Not available for bulk transport.

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/ legislation specific for the substance or mixture

Contents according to (EC) regulation No.648/2004 on detergents:

**15.2. Chemical safety assessment** A chemical safety assessment has not been carried out.

# **SECTION 16: Other information**

Hazard statements relating to ingredients (see section 3)

H225 Highly flammable liquid and vapour

H315 Causes skin irritation

H336 May cause drowsiness or dizziness

H304 May be fatal if swallowed and enters airways

H411 Toxic to aquatic life with long lasting effects

H319 Causes serious eye irritation

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure

Date of issue: 15 May 2015 Issue number: 1 Date of printing: 15 May 2015

This product should be stored, handled and used in accordance with good industrial practice and in conformity with legal regulations. The information in this data sheet is based on the present state of our knowledge and is intended to describe products from the point of view of safety requirements and thus should not be construed as guaranteeing specific properties. It is for users to satisfy themselves of the suitability of this product for their own applications.

A3BS2