

SAFETY DATA SHEET according to regulation (EC) No.1907/2006

SECTION 1: Identification of the substance/mixture and company

1.1. Product Identifier

Product code: A5XL5
Name: Carwash XL5

1.2. Product Uses Carwash wax rinse additive.

1.3. Supplier

Quadralene Ltd
Bateman Street
Derby
DE23 8JL

Phone: 01332 292500
Web: www.quadralene.co.uk
Fax: 01332 295941
Email: info@quadralene.co.uk

1.4. Emergency telephone number

Emergency telephone number: 01332 292402

SECTION 2: Hazards identification (Undiluted product)

2.1. Classification of the mixture

According to 1272/2008

Health Hazards: Asp. Tox. 1, Eye Dam. 1, Skin Corr. 1B

Physical Hazards: Not Classified

Environmental Hazards: Not Classified

2.2. Label elements

According to 1272/2008

Danger



H314 Causes severe skin burns and eye damage

H318 Causes serious eye damage

H304 May be fatal if swallowed and enters airways

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P363 Wash contaminated clothing before reuse.

P304 + P340 IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P405 Store locked up.

2.3. Other hazards

SECTION 3: Composition/ information on ingredients

Material	CAS number	Level	Hazards (see section 16)	
Hydrocarbon Solvent	64742-47-8	5-15%	Asp. Tox. 1	H304
2-(2-butoxyethoxy) ethanol	112-34-5	5-15%	Eye Irrit. 2	H319
Cationic Wax Compound	Mixture	5-15%	Aquatic Acute 1, Aquatic Chronic 1, Flam. Liq. 2, Skin Corr. 1B, STOT SE 3	H225 H314 H336 H410
Nonionic surfactant	61791-14-8	1-5%	Acute Tox. 4, Aquatic Acute 1, Eye Dam. 1, Skin Irrit. 2	H302 H315 H318 H400

SECTION 4: First aid measures

4.1. Description of first aid measures

Eye contact: Immediately flush eyes with water, holding eyelids apart, for at least 10 minutes. Seek medical assistance immediately.

Skin contact: Remove contaminated clothing, wash skin with water and seek medical attention if irritation persists.

Inhalation: Not applicable.

Ingestion: Do not induce vomiting. If conscious, give water to drink. Seek medical assistance immediately.

First aider PPE: As required to prevent contact. See section 8.2.

4.2. Most important symptoms and effects, both acute and delayed

Eye hazard: Will cause severe damage.

Skin hazard: Causes severe burns.

Respiratory hazard: Moderate toxicity. Main danger is of lung damage by aspiration.

Other hazards:

4.3. Indication of any immediate medical attention and special treatment needed

No special treatment or attention required additional to section 4.2.

SECTION 5: Fire fighting measures

Flammability hazard: Not combustible.

5.1. Extinguishing media

Not applicable.

5.2. Special hazards arising from the mixture

No specific hazards arising from the mixture.

5.3. Advice for firefighters

No special measures arising from the mixture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Take precautions to avoid contact. Use Personal Protective Equipment as detailed in section 8

Spillage may make floors slippery. Keep the area clear. Observe regulations.

6.2. Environmental precautions

Prevent spills from entering water courses.

6.3. Methods and material for containment and cleaning up

Small quantities, flush to foul sewer with a large quantity of water.

Large quantities, contain and absorb or pump into suitable containers for disposal.

6.4. Reference to other sections

Observe the advice given in sections 8 and 13

SECTION 7: Handling and storage

Shelf life: 12 months in original sealed containers.

7.1. Precautions for safe handling

Do not mix with other products. Observe good industrial hygiene.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, dry place protected from frost and away from acids and strong oxidising agents. Store upright in original containers. Recommended storage temperature 5-25°C.

7.3. Product Uses

Adjust the machine to give the required water shedding effect. Concentration at the point of application is normally between 0.5 and 0.05%

Please refer to product safety data sheet before use. Use only as directed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits

Hydrocarbon Solvent	600mg/m ³	WEL 8 hour TWA (Recommended)
2-(2-Butoxyethoxy) ethanol	67.5mg/m ³	WEL 8 hour TWA (UK EH40)

8.2. Exposure controls

These measures are suggested on the basis of general use methods and may not be appropriate to all potential uses of the product. The user is responsible for carrying out a full risk assessment of their specific processes and systems of work.

Eye protection:	Wear eye protection appropriate to the process according to BS EN 166.
Hand protection:	Wear nitrile or neoprene gloves. Exact choice of glove depends on specific risk assessments.
Body protection:	As necessary to prevent contact.
Respiratory protection:	Use in a well ventilated area. Avoid breathing vapour or spray. Not a hazard in normal use.
Other protection:	

Personal protective equipment:



Exact PPE requirements should be determined from a specific risk assessment of the processes being carried out.

Environmental protection: Prevent mixture from entering water courses.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	Yellow/green fluorescent liquid	
Odour:	Characteristic, solvent.	
pH (typical):	7.0	1% in water (typical).
Initial boiling point:	100°C.	Flash point: Not applicable.
Auto-ignition temp:	Not applicable.	Viscosity: Free flowing.
Explosive properties:	Not applicable.	
Oxidising properties:	Not applicable.	
Vapour pressure:	17.5mm Hg at 20°C.	
Solubility:	Dispersible in water.	
Relative density at 20° C (typical):	1.000	

9.2. Other information

SECTION 10: Stability and reactivity

- 10.1. Reactivity** Incompatible with strong oxidising agents and acids.
- 10.2. Chemical stability** Stable under recommended storage conditions.
- 10.3. Possibility of hazardous reactions** No hazardous reactions are expected to occur.
- 10.4. Conditions to avoid** Extremes of temperature.
- 10.5. Incompatible materials** Incompatible with strong oxidising agents and acids.
- 10.6. Hazardous decomposition products** None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

- Acute toxicity: Based on available data, the classification criteria are not met.
- Skin corrosion/ irritation: Mixture is classified as Skin Corr. 1B. See section 2.
- Serious eye damage/ irritation: Mixture is classified as Eye Dam. 1. See section 2.
- Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.
- Germ cell mutagenicity: Does not contain any ingredients classified as mutagenic.
- Carcinogenicity: Does not contain any ingredients classified as carcinogenic.
- Reproductive toxicity: Does not contain any ingredients classified as toxic for reproduction.
- STOT single exposure: Based on available data, the classification criteria are not met.
- STOT repeated exposure: Does not contain any ingredients classified as STOT RE.
- Aspiration toxicity: Mixture is classified as Asp Tox. 1. See section 2.

Routes of exposure/ symptoms

- Eye contact: Will cause severe damage.
- Skin contact: Causes severe burns.
- Inhalation: Not a hazard in normal use.
- Ingestion: Moderate toxicity. Main danger is of lung damage by aspiration.

SECTION 12: Ecological information

- 12.1. Toxicity** May affect aquatic organisms due to hydrocarbon content if released into water courses untreated.
- 12.2. Persistence and degradability** All organic ingredients are biodegradable when well diluted.
- 12.3. Bioaccumulative potential** Not expected to bioaccumulate
- 12.4. Mobility in soil** This product has high water solubility
- 12.5. Results of PBT and vPvB assessment** Contains no ingredients classified as PBT or vPvB.
- 12.6. Other adverse effects** No other adverse effects are anticipated.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of surplus product and packaging via a licenced chemical waste contractor.

SECTION 14: Transport information

- 14.1. UN number** 1760 **14.2. UN proper shipping name** Corrosive liquid, N.O.S.
- 14.3. Transport hazard class(es)** 8 **14.4. Packing group** 2
- 14.5. Environmental hazards** Not classified as environmentally hazardous for transport
- 14.6. Special precautions for user** No specific precautions.
- 14.7. Transport in bulk according to Annex II of MARPOL 7 3/78 and the IBC Code** Not available for bulk transport.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/ legislation specific for the substance or mixture

Contents according to (EC) regulation No.648/2004 on detergents:

Aliphatic hydrocarbons	5-15%	Preservative
Nonionic surfactants	<5%	
Cationic surfactants	<5%	

15.2. Chemical safety assessment A chemical safety assessment has not been carried out.

SECTION 16: Other information

Hazard statements relating to ingredients (see section 3)

H304 May be fatal if swallowed and enters airways

H319 Causes serious eye irritation

H225 Highly flammable liquid and vapour

H314 Causes severe skin burns and eye damage

H336 May cause drowsiness or dizziness

H410 Very toxic to aquatic life with long lasting effects

H302 Harmful if swallowed

H315 Causes skin irritation

H318 Causes serious eye damage

H400 Very toxic to aquatic life

Date of issue: 14 May 2015 Issue number: 1 Date of printing: 15 May 2015

This product should be stored, handled and used in accordance with good industrial practice and in conformity with legal regulations. The information in this data sheet is based on the present state of our knowledge and is intended to describe products from the point of view of safety requirements and thus should not be construed as guaranteeing specific properties. It is for users to satisfy themselves of the suitability of this product for their own applications.

